

ASHLAND®		Page: 1 of 18
		Revision Date: 03.07.2013
SAFETY DATA SHEET		Print Date: 17.07.2013
Tectyl® GLASHELDER/KLAR CORROSION INHIBITOR		MSDS Number: R0524263 Version: 2.0
VE20055		

Conforms to EU Regulation 1907/2006/EC as amended. - SDSCLP_GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Tectyl® GLASHELDER/KLAR
CORROSION INHIBITOR

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Corrosion inhibitor.
Substance/Mixture

1.3 Details of the supplier of the safety data sheet Ashland P.O. Box 8619 NL3009 AP, Rotterdam Netherlands EUSMT@ashland.com	1.4 Emergency telephone number 00-800-274-5263-3/001-606-329-5701 , or contact your local emergency telephone number at 112 Product Information +31 10 497 5000 (in the Netherlands), or contact your local CSR contact person
---	--

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (67/548/EEC, 1999/45/EC)

Extremely flammable
Dangerous for the environment

R12: Extremely flammable.
R51/53: Toxic to aquatic organisms, may cause
long-term adverse effects in the aquatic
environment.
R67: Vapours may cause drowsiness and
dizziness.

2.2 Label elements

Labelling according to EC Directives(1999/45/EC)

ASHLAND®	Page: 2 of 18
	Revision Date: 03.07.2013
SAFETY DATA SHEET	Print Date: 17.07.2013
Tectyl® GLASHELDER/KLAR CORROSION INHIBITOR	MSDS Number: R0524263 Version: 2.0
VE20055	

Hazard symbols :



Extremely flammable



Dangerous for the environment

R-phrase(s) :

R12
R51/53

Extremely flammable.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67

Vapours may cause drowsiness and dizziness.

S-phrase(s) :

S 2
S23
S24
S29/56

Keep out of the reach of children.
Do not breathe spray.
Avoid contact with skin.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

S46

If swallowed, seek medical advice immediately and show this container or label.

S51

Use only in well-ventilated areas.

Special labelling of certain mixtures :

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material.
Keep away from sources of ignition - No smoking.

2.3 Other hazards

Assessment : PBT substance , vPvB substance - not determined

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Propane	74-98-6 200-827-9	F+; R12	Flam. Gas 1; H220 Press. Gas H280	>= 15 - < 25
Hydrocarbons, C9-C11, n-alkanes, iso-	919-857-5 01-2119463258-33-xxxx	R10 Xn; R65 R66-R67	Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304	>= 15 - < 20

ASHLAND [®]	Page: 3 of 18
	Revision Date: 03.07.2013
SAFETY DATA SHEET	Print Date: 17.07.2013
Tectyl® GLASHELDER/KLAR CORROSION INHIBITOR	MSDS Number: R0524263 Version: 2.0
VE20055	

alkanes,cyclenes, <2% aromatics				
Naphtha (petroleum), hydrotreated light	64742-49-0 265-151-9	F; R11 Xi; R38 Xn; R65 R67 N; R51/53	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 15
4-Hydroxy-4- methylpentan-2- one	123-42-2 204-626-7	Xi; R36	Eye Irrit. 2; H319	>= 1 - < 2,5
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6 265-156-6 01-2119480375-34-xxxx	Xn; R65	Asp. Tox. 1; H304	>= 1 - < 2,5
2-(2-Heptadec-8- enyl-2-imidazol- 1-yl)ethanol	95-38-5 202-414-9	Xn; R22 C; R34 N; R50/53	Acute Tox. 4; H302 Skin Corr. 1B; H314 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,5 - < 1
Barium bis(dinonylnaphtha lenesulphonate)	25619-56-1 247-132-7	Xn; R20/22- R36/38	Acute Tox. 3; H301 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 0,1 - < 0,5
WEL substance:				
Dimethyl ether	115-10-6 204-065-8	F+; R12	Press. Gas H280 Flam. Gas 1; H220	>= 25 - < 40
2-Methoxy-1- methylethyl acetate	108-65-6 203-603-9	R10	Flam. Liq. 3; H226	>= 1 - < 2,5

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

ASHLAND [®]		Page: 4 of 18
		Revision Date: 03.07.2013
SAFETY DATA SHEET		Print Date: 17.07.2013
Tectyl® GLASHELDER/KLAR CORROSION INHIBITOR		MSDS Number: R0524263 Version: 2.0
VE20055		

- If inhaled : Move to fresh air.
Call a physician or poison control centre immediately.
Keep patient warm and at rest.
If unconscious place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
In case of shortness of breath, give oxygen.
- : Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off immediately with plenty of water.
- In case of eye contact : Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
Remove contact lenses.
- If swallowed : Do not induce vomiting without medical advice.
Never give anything by mouth to an unconscious person.
Consult a physician if necessary.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
Lung irritation
central nervous system excitation (giddiness, liveliness, light-headed feeling) followed by central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects
Lowered blood pressure
Abdominal pain
Lack of coordination
blood abnormalities (breakage of red blood cells)
- Risks : This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.
Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this

ASHLAND®		Page: 5 of 18
		Revision Date: 03.07.2013
SAFETY DATA SHEET		Print Date: 17.07.2013
Tectyl® GLASHELDER/KLAR CORROSION INHIBITOR		MSDS Number: R0524263 Version: 2.0
VE20055		

material.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : no data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder
Water mist

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not use a solid water stream as it may scatter and spread fire.
Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : acrid smoke and fumes
carbon dioxide and carbon monoxide
Hydrocarbons
Acetone
various hydrocarbons

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Further information : Use water spray to cool unopened containers.
Prevent fire extinguishing water from contaminating surface water or the ground water system.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

ASHLAND [®]		Page: 6 of 18
		Revision Date: 03.07.2013
SAFETY DATA SHEET		Print Date: 17.07.2013
Tectyl® GLASHELDER/KLAR CORROSION INHIBITOR		MSDS Number: R0524263 Version: 2.0
VE20055		

Personal precautions : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks).
Evacuate personnel to safe areas.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

no data available

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Open drum carefully as content may be under pressure.
Do not breathe vapours or spray mist.
For personal protection see section 8.
Provide sufficient air exchange and/or exhaust in work rooms.
Avoid exceeding of the given occupational exposure limits (see section 8).
Smoking, eating and drinking should be prohibited in the application area.
Ensure all equipment is electrically grounded and bonded before beginning transfer operations.

Advice on protection against fire and explosion : Use explosion-proof equipment.
Take measures to prevent the build up of electrostatic charge.
Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.
Keep product and empty container away from heat and sources of ignition.
No sparking tools should be used.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
Store in original container.
Keep containers tightly closed in a dry, cool and well-

ASHLAND®	Page: 7 of 18
	Revision Date: 03.07.2013
SAFETY DATA SHEET	Print Date: 17.07.2013
Tectyl® GLASHELDER/KLAR CORROSION INHIBITOR	MSDS Number: R0524263 Version: 2.0
VE20055	

ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.

Other data : Stable under recommended storage conditions.

7.3 Specific end use(s)

no data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Value type	Form of Exposure	Control parameters	Update	Basis
Dimethyl ether	115-10-6	TWA		400 ppm 766 mg/m ³	2007	EH40 WEL
Dimethyl ether	115-10-6	STEL		500 ppm 958 mg/m ³	2007	EH40 WEL
4-Hydroxy-4-methylpentan-2-one	123-42-2	TWA		50 ppm 241 mg/m ³	2007	EH40 WEL
4-Hydroxy-4-methylpentan-2-one	123-42-2	STEL		75 ppm 362 mg/m ³	2007	EH40 WEL
2-Methoxy-1-methylethyl acetate	108-65-6	TWA		50 ppm 274 mg/m ³	2007	EH40 WEL
2-Methoxy-1-methylethyl acetate	108-65-6	STEL		100 ppm 548 mg/m ³	2007	EH40 WEL
Barium bis(dinonylnaphtalenesulphonate)	25619-56-1	TWA		0,5 mg/m ³	2007	EH40 WEL
Further information:	as Ba					

8.2 Exposure controls

ASHLAND [®]		Page: 8 of 18
		Revision Date: 03.07.2013
SAFETY DATA SHEET		Print Date: 17.07.2013
Tectyl® GLASHELDER/KLAR CORROSION INHIBITOR		MSDS Number: R0524263 Version: 2.0
VE20055		

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below level of overexposure (from known, suspected or apparent adverse effects).

Personal protective equipment

- Respiratory protection : No personal respiratory protective equipment normally required.
- Hand protection : Wear resistant gloves such as:
Nitrile rubber
- Eye protection : Safety glasses with side-shields
- Skin and body protection : Wear as appropriate:
Safety shoes
Flame-resistant clothing
- Hygiene measures : Keep away from food, drink and animal feedingstuffs.
When using do not eat, drink or smoke.
Avoid contact with skin, eyes and clothing.
Ensure that eyewash stations and safety showers are close to the workstation location.

Environmental exposure controls

- General advice : Prevent further leakage or spillage if safe to do so.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : aerosol; aerosol
- Colour : colourless
- Odour : hydrocarbon-like
- Odour Threshold : no data available
- pH : no data available
- Freezing point / Melting point : < -20 °C
- Boiling point : < 35 °C
- Flash point : < -18 °C
- Evapouration rate : no data available

ASHLAND®	Page: 9 of 18
	Revision Date: 03.07.2013
SAFETY DATA SHEET	Print Date: 17.07.2013
Tectyl® GLASHELDER/KLAR CORROSION INHIBITOR	MSDS Number: R0524263 Version: 2.0
VE20055	

Flammability (solid, gas) : no data available
 Burning rate : no data available
 Lower explosion limit : no data available
 Upper explosion limit : no data available
 Vapour pressure : 3 hPa; 20 °C

 Relative vapour density : no data available
 Relative density : no data available
 Density : 0,72 g/cm³; 20 °C

 Water solubility : insoluble

 Solubility in other solvents : no data available
 Partition coefficient: n-octanol/water : no data available
 Auto-ignition temperature : no data available
 Ignition temperature : no data available
 Thermal decomposition : no data available
 Viscosity, dynamic : 45 mPa.s; 20 °C

 Viscosity, kinematic : 50 mm²/s; 20 °C

 Explosive properties : no data available
 Oxidizing properties : no data available

9.2 Other information

Bulk density : no data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Hazardous polymerisation does not occur.

ASHLAND®		Page: 10 of 18
		Revision Date: 03.07.2013
SAFETY DATA SHEET		Print Date: 17.07.2013
Tectyl® GLASHELDER/KLAR CORROSION INHIBITOR		MSDS Number: R0524263 Version: 2.0
VE20055		

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Further information: Stable under recommended storage conditions.
: Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Exposure to air.
Exposure to moisture.

10.5 Incompatible materials

Materials to avoid : aluminum
aluminium hydride
Carbon monoxide
halogens
Lead
lithium aluminum hydride
Oxygen
peroxides
Strong acids
strong alkalis
Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : acrid smoke and fumes
carbon dioxide and carbon monoxide
Hydrocarbons
various hydrocarbons

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Product

Acute oral toxicity : no data available
Acute inhalation toxicity : no data available
Acute dermal toxicity : no data available

ASHLAND®	Page: 11 of 18
	Revision Date: 03.07.2013
SAFETY DATA SHEET	Print Date: 17.07.2013
Tectyl® GLASHELDER/KLAR CORROSION INHIBITOR	MSDS Number: R0524263 Version: 2.0
VE20055	

Skin corrosion/irritation : no data available

Serious eye damage/eye irritation : no data available

Respiratory or skin sensitisation : no data available

Components:

Propane :

Acute inhalation toxicity : LC 50: 12190 ppm, 4 h, Rat,

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics :

Acute oral toxicity : LD 50: > 5.000 mg/kg, Rat

Acute inhalation toxicity : LC 50: > 5 mg/l, 4 h, Rat, OECD Test Guideline 403

Acute dermal toxicity : LD 50: > 5.000 mg/kg, Rat, OECD Test Guideline 402

4-Hydroxy-4-methylpentan-2-one :

Acute oral toxicity : LD 50: 4.000 mg/kg, Rat

Acute dermal toxicity : LD 50: 13.500 mg/kg, Rabbit

Distillates (petroleum), hydrotreated light naphthenic :

Acute oral toxicity : LD 50: > 5 g/kg, Rat

Acute dermal toxicity : LD 50: > 2.000 mg/kg, Rabbit

2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol :

Acute oral toxicity : LD 50: ca. 1.265 mg/kg, Rat

Respiratory or skin : Did not cause sensitisation on laboratory animals.

ASHLAND [®]	Page: 12 of 18
	Revision Date: 03.07.2013
SAFETY DATA SHEET	Print Date: 17.07.2013
Tectyl® GLASHELDER/KLAR CORROSION INHIBITOR	MSDS Number: R0524263 Version: 2.0
VE20055	

sensitisation

Dimethyl ether :

Acute inhalation toxicity : LC 50: 308,5 mg/l, 4 h, Rat,

2-Methoxy-1-methylethyl acetate :

Acute oral toxicity : LD 50: 8.532 mg/kg, Rat

Acute inhalation toxicity : LC 50: > 5344 ppm, 4 h, Rat,

Acute dermal toxicity : LD 50: > 5.000 mg/kg, Rabbit

SECTION 12: Ecological information

12.1 Toxicity

Product:

no data available

Components:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics:

Toxicity to fish : LC 50: > 1.000 mg/l, 96 h, *Oncorhynchus mykiss* (rainbow trout), OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC0: 1.000 mg/l, 48 h, Water flea (*Daphnia magna*), OECD Test Guideline 202

2-(2-Heptadec-8-enyl-2-imidazolin-1-yl)ethanol:

Toxicity to fish : LC 50: 0,3 mg/l, 96 h, *Danio rerio* (zebra fish), static test, OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC 50: 0,163 mg/l, 48 h, Water flea (*Daphnia magna*), semi-static test, OECD Test Guideline 202

Toxicity to algae : 0,03 mg/l, 72 h, 72 h, *Desmodesmus subspicatus* (green algae), Growth inhibition, OECD Test Guideline 201

ASHLAND [®]	Page: 13 of 18
	Revision Date: 03.07.2013
SAFETY DATA SHEET	Print Date: 17.07.2013
Tectyl® GLASHELDER/KLAR CORROSION INHIBITOR	MSDS Number: R0524263 Version: 2.0
VE20055	

M-Factor : 10

12.2 Persistence and degradability

Product:

no data available

Components:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclenes, <2% aromatics :

Biodegradability : Expected to be biodegradable

12.3 Bioaccumulative potential

Product:

Bioaccumulation : The bioaccumulation potential cannot be determined.

Components:

no data available

12.4 Mobility in soil

Product:

no data available

Components:

no data available

12.5 Results of PBT and vPvB assessment

Product:

no data available

Components:

no data available

12.6 Other adverse effects

Product:

no data available

Components:

no data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

ASHLAND [®]		Page: 14 of 18
		Revision Date: 03.07.2013
SAFETY DATA SHEET		Print Date: 17.07.2013
Tectyl® GLASHELDER/KLAR CORROSION INHIBITOR		MSDS Number: R0524263 Version: 2.0
VE20055		

- Product : Dispose of in accordance with the European Directives on waste and hazardous waste.
- : Do not contaminate ponds, waterways or ditches with chemical or used container.
Container hazardous when empty.
Dispose of in accordance with local regulations.
- Contaminated packaging : Empty remaining contents.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADR: Not dangerous goods

ADNR: Not dangerous goods

RID: Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS: UN1950

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: UN1950

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER: UN1950

14.2 UN proper shipping name

ADR: Not dangerous goods

ADNR: Not dangerous goods

RID: Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS: AEROSOLS

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Aerosols, flammable

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER: Aerosols, flammable

14.3 Transport hazard class(es)

ADR: Not dangerous goods

ADNR: Not dangerous goods

RID: Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS: 2.1

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: 2.1

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER: 2.1

14.4 Packing group

ADR: Not dangerous goods

ASHLAND [®]		Page: 15 of 18
		Revision Date: 03.07.2013
SAFETY DATA SHEET		Print Date: 17.07.2013
Tectyl® GLASHELDER/KLAR CORROSION INHIBITOR		MSDS Number: R0524263 Version: 2.0
VE20055		

ADNR: Not dangerous goods

RID: Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS:

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO:

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER:

14.5 Environmental hazards

ADR: not applicable

ADNR: not applicable

RID: not applicable

INTERNATIONAL MARITIME DANGEROUS GOODS: not applicable

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: not applicable

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER: not applicable

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Ship Type: Not applicable

Hazard code(s): Not applicable

Pollutant Category: Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso II - Directive 2003/105/EC amending Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances

Hazard class	Number	Quantity 1	Quantity 2
Extremely flammable	8	10 t	50 t
Dangerous for the environment	9b	200 t	500 t

ASHLAND [®]	Page: 16 of 18
	Revision Date: 03.07.2013
SAFETY DATA SHEET	Print Date: 17.07.2013
Tectyl® GLASHELDER/KLAR CORROSION INHIBITOR	MSDS Number: R0524263 Version: 2.0
VE20055	

Notification status

US. Toxic Substances Control Act	y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	y (positive listing)
Australia. Industrial Chemical (Notification and Assessment) Act	y (positive listing)
New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand	n (Negative listing)
Japan. Kashin-Hou Law List	n (Negative listing)
Korea. Toxic Chemical Control Law (TCCL) List	y (positive listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	y (positive listing)
China. Inventory of Existing Chemical Substances	y (positive listing)

15.2 Chemical Safety Assessment

no data available

SECTION 16: Other information

Full text of R-phrases referred to under sections 2 and 3

R10	Flammable.
R11	Highly flammable.
R12	Extremely flammable.
R20/22	Harmful by inhalation and if swallowed.
R22	Harmful if swallowed.
R34	Causes burns.
R36	Irritating to eyes.
R36/38	Irritating to eyes and skin.
R38	Irritating to skin.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

Full text of H-Statements referred to under sections 2 and 3.

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H301	Toxic if swallowed.
H302	Harmful if swallowed.

ASHLAND [®]	Page: 17 of 18
	Revision Date: 03.07.2013
SAFETY DATA SHEET	Print Date: 17.07.2013
Tectyl® GLASHELDER/KLAR CORROSION INHIBITOR	MSDS Number: R0524263 Version: 2.0
VE20055	

H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Further information

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (+31 10 497 5000).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
 BEI : Biological Exposure Index
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment

ASHLAND [®]		Page: 18 of 18
		Revision Date: 03.07.2013
SAFETY DATA SHEET		Print Date: 17.07.2013
Tectyl® GLASHELDER/KLAR CORROSION INHIBITOR		MSDS Number: R0524263 Version: 2.0
VE20055		

STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level
 ABM : Water Hazard Class for the Netherlands
 ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine
 CLP : Classification, Labelling and Packaging
 CSA : Chemical Safety Assessment
 CSR : Chemical Safety Report
 DNEL : Derived No Effect Level.
 EINECS : European Inventory of Existing Commercial Chemical Substances.
 ELINCS : European List of Notified Chemical Substances
 PEC : Predicted Effect Concentration
 PEL : Permissible Exposure Limits
 PNEC : Predicted No Effect Concentration
 R-phrase : Risk phrase
 REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals
 RID : Regulation Concerning the International Transport of Dangerous Goods by Rail
 S-phrase: Safety phrase
 WGK : German Water Hazard Class