

FARECLA PROFILE POLYMER UV WAX

Page: 1

Compilation date: 18/10/2016

Revision date: 13/03/2019

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: FARECLA PROFILE POLYMER UV WAX

Product code: PRW101, PRW106

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC31: Polishes and wax blends.

1.3. Details of the supplier of the safety data sheet

Company name: Farecla Products Limited Broadmeads

Ware	

	Ware
	Hertfordshire
	SG12 9HS
	UK
Tel:	+44 (0)19 2046 5041 8:30-16:30 (Monday to Friday)
Fax:	+44 (0)19 2046 6557
Email:	technical@farecla.com

1.4. Emergency telephone number

Emergency tel: +44 (0)20 7188 0300 (24 hours)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: -: EUH208

Most important adverse effects: Contains 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

Precautionary statements: P102: Keep out of reach of children.

P412: Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

FARECLA PROFILE POLYMER UV WAX

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS - REACH registered number(s): 01-2119463258-33

EINECS	CAS	PBT / WEL	CLP Classification	Percent
919-857-5	-	-	Flam. Liq. 3: H226; STOT SE 3: H336;	10-30%
			Asp. Tox. 1: H304; -: EUH066	

DISTILLATES (PETROLEUM) HYDROTREATED MIDDLE - REACH registered number(s): 01-2119457735-29-0003

919-029-3	64742-46-7	Substance with a Community	Asp. Tox. 1: H304; -: EUH066	1-10%
		workplace exposure limit.		

1,2-BENZISOTHIAZOLIN-3-ONE

220-120-9	2634-33-5	-	Acute Tox. 4: H302; Skin Irrit. 2: H315;	<1%
			Eye Dam. 1: H318; Skin Sens. 1:	
			H317; Aquatic Acute 1: H400	

Contains: Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclics, <2% Aromatics

Distillates (Petroleum) Hydrotreated Middle

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

Page: 2

FARECLA PROFILE POLYMER UV WAX

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-

side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Not applicable.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Not applicable.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Workplace exposure limits:

Respirable dust

State 8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
------------------	--------------	------------	--------------

FARECLA PROFILE POLYMER UV WAX

Page: 4

	EU	1200mg/m3, 197ppm	-	-	-	
l	DISTILLATES (PETROLEUM) HYDROTREATED MIDDLE					
	EU	5 mg/m3	-	-	-	
D	DNEL/PNEC Values					

Hazardous ingredients:

1,2-BENZISOTHIAZOLIN-3-ONE

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation (developmental tox)	111	Consumers	Systemic

8.2. Exposure controls

Engineering measures: Not applicable.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: No special requirement.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Liquid		
Colour:	Pink		
Odour:	Pleasant		
Evaporation rate:	Slow		
Oxidising:	Non-oxidising (by EC criteria)		
Solubility in water:	Slightly soluble		
Also soluble in:	No data available		
Viscosity:	Viscous		
Kinematic viscosity:	7000		
Viscosity test method:	Brookfield @ 20degC		
Boiling point/range℃:	No data available.	Melting point/range °C:	No data available.
Flammability limits %: lower:	No data available.	upper:	No data available.
Flash point ℃:	>93 Part.c	coeff. n-octanol/water:	No data available.
Autoflammability℃:	No data available.	Vapour pressure:	No data available.
Relative density:	0.960	pH:	Approx. 7
VOC g/I:	131		

9.2. Other information

Other information: Not applicable.

FARECLA PROFILE POLYMER UV WAX

Page: 5

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

DERMAL	RBT	LD50	>5000	mg/kg
DUST/MIST	RAT	4H LC50	4951	mg/l
ORAL	RAT	LD50	>5000	mg/kg

DISTILLATES (PETROLEUM) HYDROTREATED MIDDLE

DERMAL	RBT	LD50	>3160	mg/kg
ORAL	RAT	LD50	>5000	mg/kg
VAPOURS	RAT	4H LC50	>5266	mg/l

1,2-BENZISOTHIAZOLIN-3-ONE

ORL	MUS	LD50	1150	mg/kg
ORL	RAT	LD50	1020	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

FARECLA PROFILE POLYMER UV WAX

Inhalation: No symptoms.

Delayed / immediate effects: No data available.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Daphnia magna	48H EC50	1000	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H ErC50	>1000	mg/l

DISTILLATES (PETROLEUM) HYDROTREATED MIDDLE

FISH	96H LC50	1028	mg/l
Invertebrate	48H LL50	>3000	mg/l
MARINE ALGAE (Skeletonema costatum)	72H ErC50	3198	mg/l
MARINE ALGAE (Skeletonema costatum)	72H IC50	3198	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal
	company.
Recovery operations:	Not applicable.
Waste code number:	08 04 12
Disposal of packaging:	Dispose of as normal industrial waste.
NB:	The user's attention is drawn to the possible existence of regional or national
	regulations regarding disposal.

FARECLA PROFILE POLYMER UV WAX

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information:	according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation
	(EU) 2015/830
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking.
	EUH208: Contains 1,2-benzisothiazolin-3-one. May produce an allergic reaction.
	H226: Flammable liquid and vapour.
	H302: Harmful if swallowed.
	H304: May be fatal if swallowed and enters airways.
	H315: Causes skin irritation.
	H317: May cause an allergic skin reaction.
	H318: Causes serious eye damage.
	H336: May cause drowsiness or dizziness.
	H400: Very toxic to aquatic life.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.